

CONO canto



The elegant lighting track loudspeaker

The high-quality track loudspeaker for perfect integration

The CONO canto track loudspeaker is equipped with a special connection for use in all commercially available 3-phase tracks, compatible with all Nordic Aluminium and Eutrac lighting tracks, as well as all other manufacturers that use this standard. This means that no cables are visible. The loudspeaker housing is made of glass fibre reinforced plastic and can be used directly next to spotlights. The special paint finish ensures an elegant and scratch-resistant surface structure. With a diameter of 135 mm and a height of 187 mm, it is handy and unobtrusive. The track loudspeakers are available as a cable version for 100 volt PA systems and as 16Ω version. For those who want it really simple, quick and completely cable-free, there are also our SMART track speaker, which are connected to the audio source via radio.

Technical Data

Application

Lighting-track mounting

Design

Colours



Dimensions

ø 134 mm x 187 mm (incl. adapter)

Material housing

ABS plastic - glass fibre reinforced

Sound

	CONO canto 50	CONO canto V
Principle	Full-range 360°	Full-range 360°
Nominal power	50 W / 90 W	50 W / 90 W
Impedance	16 Ω	16 Ω
Sensitivity	83,4 dB	83,4 dB
Maximum SRL	100 dB	100 dB
Frequency range	117-21.000 Hz	117-21.000 Hz

Installation

	CONO canto 50	CONO canto V
Weight	980 g	1,25 kg
Power supply	Block terminal	Block terminal