

CONO puro SMART



The smart built-in loudspeaker

Pure optics for pure sound - minimalist design and quick installation with twist lock

The new CONO puro built-in loudspeaker fits perfectly with the "small and simple" design trend. The diameter is just 150mm. The music is received reliably via 1.9 GHz radio technology. Furthermore, the new quick-release fastener eliminates the need for screws. This allows for quick installation and the screwless design also ensures simple elegance. The material thickness of the ring is kept to a minimum so that the speaker can lie flat on the ceiling. The ceiling cut-out required for installation is 120 mm and the installation depth is 140 mm.

Technical Data

Application	In-ceiling loudspeaker
Design	
Colours	● ○ ●
Dimensions	Ø 150 mm / h: 160 mm
Material housing	Ring made from glass fibre reinforced ABS plastic
Sound	
Principle	360° - Speaker with integrated amplifier and wireless module
Output power	40 W RMS
Equipment	NewTec KA10 loudspeaker 50W 4Ω
Efficiency	85,5 dB
Maximum SRL	102 dB
Frequency response	105-20.000 Hz
Radio frequency	1,9 GHz n-DECT
Transmitter	SMARTplayer
Installation	
Ceiling cut-out	120 mm
Ceiling thickness	mind. 6 mm / max. 25 mm
Installation depth	140 mm
Weight	648 g
Power supply	AC 100-240 V; 50/60 Hz; 0.5 A
Connections	Connection terminal