

CONO canto



The elegant lighting track loudspeaker

The high-quality track loudspeaker for perfect integration

The CONO canto track loudspeaker is equipped with a special connection for use in all commercially available 3-phase tracks, compatible with all Nordic Aluminium and Eutrac lighting tracks, as well as all other manufacturers that use this standard. This means that no cables are visible. The loudspeaker housing is made of glass fibre reinforced plastic and can be used directly next to spotlights. The special paint finish ensures an elegant and scratch-resistant surface structure. With a diameter of 135 mm and a height of 187 mm, it is handy and unobtrusive. The track loudspeakers are available as a cable version for 100 volt PA systems and as 16Ω version. For those who want it really simple, quick and completely cable-free, there are also our SMART track speaker, which are connected to the audio source via radio.

Technical Data

Application

Lighting-track mounting

Design

Colours



Dimensions

∅ 134 mm x 187 mm (incl. adapter)

Material housing

Glass fibre reinforced ABS plastic

Sound

Principle

CONO canto 50

Full-range 360°

CONO canto V

Full-range 360°

Nominal power

50 W / 90 W

5-10-20 W regolabile

Impedance

16 Ω

100 V / 1,9k - 940 - 470 Ω

Efficiency

83,4 dB

86,8 dB

Maximum SRL

100 dB

99,5 dB

Frequency response

117-21.000 Hz

110-21.000 Hz

Installation

Weight

CONO canto 50

980 g

CONO canto V

1,25 kg

Power supply

Block terminal

Block terminal